



Product Information Card

TINTEGGIO

Milk of lime paint

Description

Tinteggio by **Wilson & Morris** milk of lime is made of seasoned slaked lime, acrylics reinforcements and colored with natural earth oxides. Suitable for applications on old plasters and new ones of mineral nature, for mineral finishes in buildings of particular artistic interest.

It achieves soft colors and makes the media on which it is applied inique.

It has a pleasant aesthetic aspect, together with resistance in time and ease of application.

For interior walls.

Application and preparation of substrates:

Make sure all surfaces are clean and free of grease and dust.

On all surfaces, apply **SILOX PRIMER WM** (see product data sheet), only after removing the old paint not properly anchored.

Pay more attention if you have to apply **TINTEGGIO** in dark tones.

Stir well before use and dilute to 30-40% with water.

Tinting applied by brush.

Apply subsequent coats leaving 24 h.

Warnings

Do not apply if temperatures are below 8° C and above 30 ° C, and in conditions of excessive humidity conditions (<75%).

Make sure that the batch numbers are the same, or mix prior to use.

Check the color before use, as the company is not responsible for any additional costs arising from the misapplication of non-compliant colors.

The material must be protected from frost and strong temperature changes during the entire application process.

Tool cleaning

Clean the tools immediately after use with hot and running water; use a detergent for best results.



Coverage

8-9 mq/L by hand depending on the surface.

Colors

White or colored with colors by Wilson & Morris color folder.

Packaging

The packaging of Wilson & Morris TINTEGGIO product are: 5 lt, 10 lt

Storage

The material has a shelf life of 12 months in the jar, stored under cover, tightly sealed, original packaging, undiluted and at a temperature between +5 ° C and +30 ° C.

Product identification

Formulation: based on a mixture of lime

Physical state: Liquid

Appearance: Opaque

Vapor permeability Sd = 0.004 m

Factor to the spread of resistance: 40

Real content VOC 30 g / L

Maximum allowed limit (grams per liter) 40 g / L

Category

All **Wilson & Morris** products comply with laws regarding volatile organic compounds required by recent European regulations.

Safety signs

The product does not require labeling in accordance with D.L. 65 of 14/03/03 and subsequent amendments. Use the product according to current standards of safety and hygiene. After use, do not litter containers in the environment. Allow the residue to dry before disposal in accordance with current regulations.

Keep out of reach of children. In case of contact with eyes, rinse immediately with plenty of water. In cases of ingestion, seek medical advice immediately and show the container and the data sheet.

Do not empty into drains, water courses and onto the ground.

For more information, refer to the MSDS.

WILSON & MORRIS

PITTURE DECORATIVE

The information in this data sheet are based on our best experience, they must be considered as general guidance and is given in good faith but without warranty; the card does not therefore imply any responsibility on the part of Wilson & Morris company for product applications outside of our direct control.

We accept no responsibility for the performance of products resulting from their use, beyond the value of the goods supplied by us. This does not affect your statutory rights.