

Product Information Card

EMULSION EGGSHELL

Painting "egg shell"

Description

EMULSION EGGSHELL by Wilson & Morris is a glaze with eggshell finish, matt, smooth, extremely robust and high quality. It is washable and suitable for decoration of walls and wooden substrates and metal, including radiators.

Use

EMULSION EGGSHELL can be applied to all surfaces after the use of appropriate primers. A film that protects against mold and microorganisms.

Application and preparation

Wall surfaces: Ensure that all surfaces are clean and free of grease and dust.
Apply **EMULSION PRIMER** (see product data sheet) for optimum uniformity in order to get a full appearance of the color depth.
Wood surfaces: apply a **UNDERPRIMER** diluted to 20% with water as isolation.
Metal surfaces: apply a **UNDERPRIMER** diluted 15% with water.
EMULSION EGGSHELL dilute 5-10% with water and apply two coats by brush or roller.
You may experience peeling if you proceed to repaint on precarious surfaces without primer paint layers.
If you need to apply dark shades and very bright, there is the possibility of the need to apply three coats.

Warnings

Do not apply at temperatures below 10 ° C and above 30 ° C and in conditions of excessive humidity conditions (<80%).
Make sure that the batch numbers are the same, or mix prior to use.
Check the color before use, as the company is not responsible for any additional costs arising from the misapplication of non-compliant colors.
The material must be protected from frost and strong temperature changes during the entire application process.

Tool cleaning

Clean the tools immediately after use with hot and running water; use a detergent for best results.



Coverage

12-14 mq / tl per coat according to the surface.

Colors

White or colored with colors of the color chart of Wilson & Morris.

Packaging

The packaging of **Wilson & Morris EMULSION EGGSHELL** product are: 0.75 lt, 3 lt.

Storage

The material has a shelf life of 12 months in the jar, stored under cover, tightly sealed, original packaging, undiluted and at a temperature between + 5 ° C and + 35 ° C.

Product identification

Formulation: based on a mixture of copolymers in emulsion

Appearance: thick liquid

Appearance: Opaque

Wet abrasion resistance according to UNI-EN 13300: class 1

VOC content of 66 g / L

Maximum allowed limit (grams per liter) 130 g / L

Category

All **Wilson & Morris** products comply with laws regarding volatile organic compounds required by recent European regulations.

Safety signs

EMULSION EGGSHELL by **Wilson & Morris** is an eco-friendly product, which complies with the regulations on volatile organic compounds (VOC) set by European legislation.

Ensure good ventilation during application and drying.

The product does not require labeling in accordance with D. L. 65 of 14/03/03 and subsequent amendments. Use the product according to current standards of safety and hygiene. After use, do not litter containers in the environment. Allow the residue to dry before disposal in accordance with local regulations.

Keep out of reach of children. In case of contact with eyes, rinse immediately with plenty of water. In cases of ingestion, seek medical advice immediately and show the container and the data sheet.

Do not empty into drains, water courses and onto the ground.

WILSON & MORRIS

PITTURE DECORATIVE

For more information, refer to the MSDS.

The information in this data sheet are based on our best experience, they must be considered as general guidance and is given in good faith but without warranty; the card does not therefore imply any responsibility on the part of Wilson & Morris company for product applications outside of our direct control.

We accept no responsibility for the performance of products resulting from their use, beyond the value of the goods supplied by us. This does not affect your statutory rights.