

WILSON & MORRIS

PITTURE DECORATIVE

Product Information Card

MATT EMULSION

High-quality matte painting

Description

MATT EMULSION by Wilson & Morris is a water-based paint with a matte look finish and velvety to the touch; high quality, suitable for interior decorating walls and ceilings. It can be applied on all surfaces, such as old and new plasters, lime based cement, plasterboard and wood, after appropriate preparation of the supports.

Application and preparation

Make sure all surfaces are clean and free of grease and dust.

On all surfaces, apply **EMULSION PRIMER** (see product data sheet) to obtain an excellent uniformity, in order to get a full effect of the color depth.

You may experience peeling if you proceed to repaint on precarious surfaces without primer paint layers.

Pay more attention if you have to apply **EMULSION MATT** in dark tones.

Do not stack wet paint on the sides of the dry paint, as you might experience in the application fault called "Flashing": darker streaks and different brightness at the overlap.

Stir well before use and dilute with water to 30- 35% for light colors.

Proceed with a lower dilution, about 15-20% with water for dark tones.

Do not apply to fresh slightly acidic media, allow an adequate curing time, which can range from three to five weeks.

Warnings

Do not apply at temperatures below 10 ° C and above 30 ° C and in conditions of excessive humidity conditions (<80%).

Make sure that the batch numbers are the same or mix prior to use.

Check the color before use, as the company is not responsible for any additional costs arising from the misapplication of non-compliant colors.

The material must be protected from frost and strong temperature changes during the entire application process.

Tool cleaning

Clean the tools immediately after use with hot and running water; use a detergent for best results.

Coverage

12mq/lt by hand depending on the surface.



Colors

White or colored with colors of the color chart of **Wilson & Morris**.

Packaging

The packs of **Wilson & Morris MATT EMULSION** product are: 100 ml, 2.5 lt, 5 l, 10 l.

Storage

The material has a shelf life of 12 months in the jar, stored under cover, tightly sealed, original packaging, undiluted and at a temperature between + 5° C and + 35 ° C.

Product identification

Formulation: based on a mixture of copolymers in emulsion

Appearance: thick liquid

Appearance: Opaque

Wet abrasion resistance according to UNI-EN 13300: class 1

Permeability UNI-EN 1062-1 vapor: Class 2

real content VOC 26 g / L

Maximum allowed limit (grams per liter) 30 g / L

Category

All **Wilson & Morris** products comply with laws regarding volatile organic compounds required by recent European regulations.

Safety signs

The product does not require labeling in accordance with D. L. 65 of 14/03/03 and subsequent amendments. Use the product according to current standards of safety and hygiene. After use, do not litter containers in the environment. Allow the residue to dry before disposal in accordance with current regulations.

Keep out of reach of children. In case of contact with eyes, rinse immediately with plenty of water. In cases of ingestion, seek medical advice immediately and show the container and the data sheet.

Do not empty into drains, water courses and onto the ground.

For more information, refer to the MSDS.

The information in this data sheet are based on our best experience, they must be considered as general guidance and is given in good faith but without warranty; the card does not therefore imply any responsibility on the part of Wilson & Morris company for product applications outside of our direct control.

We accept no responsibility for the performance of products resulting from their use, beyond the value of the goods supplied by us. This does not affect your statutory rights.